MezzoLite

MezzoLite

The MezzoLite LED Exit Sign provides an excellent viewing distance of 30metres and although still a 'box' design it offers much better aesthetics when compared to conventional exit boxes. MezzoLite Exit Sign luminaires feature attractive Polycarbonate enclosures with a sloping front opal panel and screen printed safety sign legends. The integral rechargeable batteries and charger/driver PCB are mounted on the back surface and the advanced wide angle white LEDs provide even and effective illuminance across the legend.



MEZ/M3/WH/ECAR

OPERATION


The MezzoLite range is supplied with Maintained operation as standard providing 3 hour duration. (Non-maintained operation is available by excluding a switched live supply). Pictogram legend panels complying with the EC Safety Signs Regulations and latest ISO sign requirements are available.

The luminaire fully complies to the requirements of EN60598.2.22 and offers bright and even luminance across the legend panel ensuring maximum visibility in the event of an emergency.



GENERAL SPECIFICATION

Construction	Injection moulded polycarbonate		
S upply Voltage	230Volt (220-240V) ~ 50Hz		
Light S ource	16 x white LEDs		
S upply Current	Maintained: 45mA Mains: 30mA		
Light Output	>100 lumens		
Battery	3 cell 2Ah Nickel Cadmium		
Cable Entry	20mm knock-outs top and back		
Dimensions (max)	33mm (L) x 75mm (W) x 160mm (H)		







MezzoLite

SPECIFICATION

OPERATION	Maintained	Mains only	
Light source	16 x wide angle white LEDs		
Light output (mains)	100lm	100lm	
Light output (emergency)	100lm	_	
Battery	3 x 2Ah NiC d	_	
Charge current	100mA	_	
Recharge period	24 hours (max)	_	
Input voltage	230Volt +/- 10% ~ 50Hz		
Power (maximum)	4VA (max.)	<4VA	
Weight	2.4kg	2.3kg	



EC Signs Directive format



ISO sign format

ORDER CODES	Description		
MEZ/NM3/WH	Maintained LED Exit Sign luminaire		
MEZ/230/WH	Mains only LED Exit Sign luminaire		
OPTIONS: /DALI	Self-Test	or DALI operation	
LEGENDS:	/ECAR /ECAL /ECAD /ISOAR /ISOAL /ISOAU	EC format — Arrow Right EC format — Arrow Left EC format — Arrow Down ISO format — Arrow Right ISO format — Arrow Left ISO format — Arrow Up	



