



Marine Outdoor

The ultimate exit luminaire for the outdoor areas leading to the lifeboats

SPECIFICATIONS	MARINE OUTDOOR B 315x70	MARINE OUTDOOR B 315x150
Input Voltage	230 V AC/DC (0/50/60Hz)	
Power consumption	< 8 W / 15 VA	
Protection class	I	
Light source	LED	
Viewing distance	< 14 m	< 30 m
Ingress protection	IP67	
Cable (length)	Halogen-free (0.5 m)	
Connector	Wieland	
Mouting options	Surface	
Standards	SOLAS II-1/42-1 (MSC.11(55)) ⁽¹⁾ , EN 1838 ⁽²⁾	
Country of origin	Finland	

⁽¹⁾ Supplementary emergency lighting: For ro-ro passenger ships SOLAS II-1/42-1 (MSC.11(55))

⁽²⁾ The illuminated signs comply with the photometric requirements of EN 1838.

- single sided signs are illuminated only on frontside to prevent misleading information from behind
- double sided signs consists of two elements, both illuminated evenly



MATERIALS	
Housing	White acid-resistant (A4) sheet metal
Sign	Acrylic

DIMENSIONS	MARINE OUTDOOR B 315x70	MARINE OUTDOOR B 315x150
Length x Width x Height	364 x 164 x 110 mm	364 x 244 x 110 mm
Weight	3 450 g	3 900 g

ORDERING	
ITEM #	DESCRIPTION
	MARINE OUTDOOR B 315X70, SINGLE SIDED
	MARINE OUTDOOR B 315X70, DOUBLE SIDED
	MARINE OUTDOOR B 315X150, SINGLE SIDED
	MARINE OUTDOOR B 315X150, DOUBLE SIDED

SPARE PARTS	
ITEM #	DESCRIPTION
	LED TUBE